ARDON®
WORKWEAR
& OUTDOOR

ARDON®V2011

SAFETY GLASSES



UV

TECHNICAL DATA

© ARDON s.r.o. / ALL RIGHTS RESERVED
ARDON s.r.o. tř. Kosmonautů 1221/2a, Olomouc www.ardon.cz

ARDON®V2011

SAFETY GLASSES

ARTICLE NO. **E4020**



Lens materiál	Polycarbonate
Temple materiál	Nylon
Material frame	Nylon
Lens	clear

TECHNICAL DATA

DESCRIPTION

Safety glasses with dark blue nylon frame and temples. This glasses perfectly fit to every user thanks to adjustable lenght of temples. Large clear polycarbonate lens which are made from one piece protect against UV radiation and are resistant to lowenergy shocks (up to 45 m/s) at extreme temperatures (-5°C - +55°C). They provide maximum protection and extremely wide field of vision.

© ARDON s.r.o. / ALL RIGHTS RESERVED

STANDARDS

This personal protective equipment complies with the requirements of the following harmonized standard:

EN ISO 16321-1:2022/A1:2025 **Eye and face protection for occupational use** - Part 1: General Requirements

EN 166:2001: **Personal yey protection equipment - Basic requirementrs**

The protective eyewear complies with the requirements of Regulation (EU) 2016/425 of the European Parliament and of the Council on personal protective equipment and Regulation (EU) 2023/998 of the European Parliament and of the Council on general product safety.

Certification was carried out by Notified Body No. 0598 (SGS Fimko Oy, Takomotie 8, FI-00380 Helsinki, Finland), Certificate No. 0598/PPE/26/1326, dated 28 April 2026.

Lens clear, UV 380, A UL 1,2 CT 1 CE

Filtre type	GL	UV filter
Shade number	1,2	clear
Optical class	1	Permanent wear
Mechanical resistance	CT	Resistence to low-energy particle impacts at extreme temperatures
Anti-fog lens	x	
Scratch resistant coating	x	
UV protective coating	✓	

TECHNICAL DATA

© ARDON s.r.o. / ALL RIGHTS RESERVED

NUMBER OF PIECES IN CARTON	250 pc
QUANTITY PER BOX	10 pc
CARTON WEIGHT	12 kg
CARTON SIZE	0,103 m^3
UNIT PACKAGING	1 pc



The product must be stored in its packaging in a dry, clean place, away from direct sunlight, at temperatures between +5°C and +55°C, with relative humidity up to 90%, and away from sources of gasoline or solvent vapors.

Cleaning is recommended after each use. Clean at room temperature using a soft cloth lightly moistened with a diluted solution of water and mild detergent.

Do not use hot water, gasoline, degreasers, organic solvents, or abrasive cleaning agents.

TECHNICAL DATA

© ARDON s.r.o. / ALL RIGHTS RESERVED
ARDON s.r.o. tř. Kosmonautů 1221/2a, Olomouc www.ardon.cz