



ARDON®
WORKWEAR
& **OUTDOOR**

ARDON® DIGGER S1P

SAFETY SHOES



DRY AIR



**DEFUSE
CONTROL**



NONMETALLIC



REFLECTIVE

TECHNICAL SHEET



ARDON®
WORKWEAR
& OUTDOOR

ARDON® DIGGER S1P

SAFETY SHOES

ARTICLE

G3161

MATERIAL

Upper
Lining
Sole
Toe cap
Plate
Insole

MICROFIBER / CANVAS type fabrics
MESH laminated breathable fabric
MD/rubber/TPU, glued technology
composite 885
kevlar
ANATOMIC FOAM anatomically shaped EVA foam

SIZE

38 - 48

UNIT

pair

PACKAGE

Units in a carton
Units in a box

10 pairs
1 pair

DIMENSIONS

Carton H x W x D
(cm)
Carton (cbm)

38 - 43
34 x 48.5 x 63
0,104

44 - 48
37 x 52.5 x 63
0,122

Size EUR	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51
Insole length mm	-	-	-	251	258	264	271	278	284	291	298	304	311	318	-	-	-
Foot length cm	-	-	-	24,6	25,3	25,9	26,6	27,3	27,9	28,6	29,3	29,9	30,6	31,3	-	-	-

DESCRIPTION

Low shoes in sports design. Breathable upper is made of solid fabric and microfiber, the toe cap is reinforced with PU. Wearing comfort is increased by padding the tongue and the area around the heel and ankle, but mainly the shoes are equipped with an anatomically shaped insole, made of a material that effectively dampens the impact of the tread and ensures comfort even during long-term wear. The sole made of a combination of MD / rubber / TPU material ensures a soft tread and at the same time provides the highest level of anti-slip properties.

TECHNICAL SHEET



ARDON®
WORKWEAR
& OUTDOOR

NORMS

(EU) 2016/425

EN ISO 20345:2011

Personal protective equipment – Safety footwear

Category

S1P SRC

Categories

EN ISO 20345

E - energy absorption in the heel area

✓



FO - resistance to oils and fuels

✓



A - antistatic footwear

✓



SRC - resistance to slipping on ceramic floor tiles with SLS
and on steel floors with glycerin

✓



WR - upper resistant to water



Safety toe cap for toe protection

✓



P - resistance to punctures (protective insole)

✓



SRA - slip resistance ceramic floor tiles with SLS



HRO - resistance to contact heatup to 300 °C



HI-insulation of the bottom of the shoe against heat



CI-insulation of the bottom of the shoe against the cold



Splatters of molten metal



ESD – shoe protects against electrostatic discharge and can
be used on EPA premises



The shoes do not contain metal parts

✓



-

-

-



ARDON®
WORKWEAR
& OUTDOOR

CODE	EAN	CARTON WEIGHT (KG)	UNIT WEIGHT (KG)
G3161/38	8592390157416	12.90	1.290
G3161/39	8592390068620	13.10	1.310
G3161/40	8592390068637	13.30	1.330
G3161/41	8592390068644	13.60	1.360
G3161/42	8592390068651	13.90	1.390
G3161/43	8592390068668	14.20	1.420
G3161/44	8592390068675	14.70	1.470
G3161/45	8592390068682	15.60	1.560
G3161/46	8592390068699	16.00	1.600
G3161/47	8592390068705	16.30	1.630
G3161/48	8592390068712	16.60	1.660

TECHNICAL SHEET



ARDON®
WORKWEAR
& OUTDOOR



TECHNICAL SHEET



ARDON®
WORKWEAR
& OUTDOOR

