



ARDON®
WORKWEAR
& **OUTDOOR**

ARDON® PETRAX DOUBLE

MULTIFUNCTIONAL HANDLING IN DRY AND WET ENVIRONMENTS
WITH THE POSSIBILITY OF HEAT PROTECTION



EN 388: 2016



EN 407: 2004

TECHNICAL DATA



ARDON®
WORKWEAR
& OUTDOOR

ARDON® PETRAX DOUBLE

MULTIFUNCTIONAL HANDLING IN DRY AND WET ENVIRONMENTS
WITH THE POSSIBILITY OF HEAT PROTECTION

CODE **A8107**

MATERIAL

Lining 15G polyester
Coating ¾ latex (red) + ½ latex foam (black)
Thickness 1,4 mm (in palm)

SIZE(S) 7 / S – 11 / 2XL

UNIT pair

PACKING


Units in carton 240 pairs → 120 pairs *change of cardboard in 2. ½ 2022*
Units in polybag 12 pairs
Retail packaging sales label, size 10 / XL also without sales label

DIMENSIONS

| | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 |
|-----------------------|---|---|----------|----------|----------|----------|----------|----|
| Carton H x W x D (cm) | - | - | 43x27x34 | 43x27x34 | 43x27x34 | 43x28x35 | 43x28x35 | - |
| Carton (cbm) | - | - | 0,0395 | 0,0395 | 0,0395 | 0,0421 | 0,0421 | - |

WEIGHT

| | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 |
|-------------|---|---|------|------|------|------|------|----|
| Carton (kg) | - | - | 8,60 | 9,50 | 10,2 | 10,9 | 11,6 | - |
| Unit (g) | - | - | 55,0 | 62,0 | 68,0 | 74,0 | 80,0 | - |



Size chart (cm)

| | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 |
|------------------|---|---|------|------|------|------|------|----|
| Total length (A) | - | - | 23,0 | 24,0 | 25,0 | 26,0 | 27,0 | - |
| Cuff length (B) | - | - | 7,10 | 7,30 | 7,50 | 7,70 | 7,90 | - |
| Cuff width (C) | - | - | 7,80 | 8,00 | 8,20 | 8,40 | 8,60 | - |
| Palm width (D) | - | - | 9,80 | 10,3 | 11,0 | 11,2 | 11,5 | - |

Tolerance (A) ± 0,50 (cm)
Tolerance (B) ± 0,70 (cm)

Tolerance (C) ± 0,70 (cm)
Tolerance (D) ± 0,70 (cm)

DESCRIPTION

Comfortable knit with double latex dipping, waterproof and with a secure grip.



ARDON®
WORKWEAR
& OUTDOOR

STANDARDS

(EU) 2016/425

EN ISO 21420:2020 Protective gloves – general requirements and test methods

EN 388:2016 + A1:2018 Protective gloves against mechanical risks

| PROTECTION LEVELS | | | |
|-------------------------|----------------------------|------------|--------------|
| MECHANICAL RISKS | | LVL | score |
| <p>EN 388</p> | abrasion resistance | 2 | 500 – 2.000 |
| | cut resistance | 1 | 1,2 – 2,5 |
| | tearing resistance | 4 | > 75 |
| | puncture resistance | 1 | 20 – 60 |
| | cut resistance acc. to ISO | X | not measured |
| | | | unit |
| | | | cykles |
| | | | index |
| | | | N |
| | | | N |
| | | | N |

EN 407:2004

Protective gloves against heat or flame

| PROTECTION LEVELS | | | |
|----------------------|--|------------|---------------|
| THERMAL RISKS | | LVL | score |
| <p>EN 407</p> | resistance to burning | X | not measured |
| | resistance to contact heat | 2 | 250°C for 15s |
| | resistance to convective heat | X | not measured |
| | resistance to radiant heat | X | not measured |
| | resistance to small drops of molten metals | X | not measured |
| | resistance to large drops of molten metals | X | not measured |
| | | | |

SPECIAL FEATURES

- functional double dipping:
 - the base layer of smooth latex acts as a barrier against liquids
 - outer layer of latex foam allows a secure grip (even on wet objects)
- for work in both dry and wet environments, for example with loose mixtures with water (building mixtures, mortar, paints, etc.)
- protection against heat up to 150 ° C (according to certification up to 250 ° C for 15 seconds, but we generally do not recommend exposure to temperatures higher than 150 ° C, during which latex secondary vulcanizes and heats up)
- mandatory information on inner label = ARDON® design
- each pairs in each size is retail ready packed, size 10 / XL also without sales label



ARDON®
WORKWEAR
& OUTDOOR

Retail packaging (with sales label)

A8107/07-SPE

A8107/08-SPE

A8107/09-SPE

A8107/10-SPE

A8107/11-SPE

Basic packaging (without sales label)

A8107/10

EAN

8592390012814

8592390075611

8592390075628

8592390075635

8592390041685

8592390373823



ARDON®
WORKWEAR
& OUTDOOR



TECHNICAL DATA