



ARDON®
WORKWEAR
& OUTDOOR

ARDON® PRIME SANTREK S1

SAFETY SHOES



DRY AIR

TECHNICAL SHEET



ARDON®
WORKWEAR
& OUTDOOR

ARDON® PRIME SANTREK S1

SAFETY SHOES

ARTICLE G1303

MATERIAL

Upper brushed cowhide VELUR
 Lining MESH laminated breathable fabric
 Sole PU/PU, two-component spray coating, oil resistant, anti-static, antislip
 Toe cap steel 604
 Plate -
 Insole AIR COMFORT- richly perforated, perfectly removes moisture

SIZE 36-48

UNIT pair

PACKAGE

Units in a carton 10 pairs
 Units in a box 1 pair

DIMENSIONS

| | 36-41 | 42-44 | 45-48 |
|-----------------------|------------------|--------------|---------------|
| Carton H x W x D (cm) | 59,5 x 32,5 x 40 | 62 x 34 x 42 | 64,5 x36 x 44 |
| Carton (cbm) | 0,0774 | 0,0885 | 0,1021 |

| Size EUR | 35 | 36 | 37 | 38 | 39 | 40 | 41 | 42 | 43 | 44 | 45 | 46 | 47 | 48 | 49 | 50 | 51 |
|------------------|----|------|------|------|------|------|------|------|------|------|------|------|------|------|----|----|----|
| Insole length mm | - | 235 | 241 | 248 | 255 | 262 | 270 | 276 | 283 | 290 | 297 | 304 | 310 | 317 | - | - | - |
| Foot length cm | - | 23,0 | 23,6 | 24,3 | 25,0 | 25,7 | 26,5 | 27,1 | 28,3 | 28,5 | 29,2 | 29,9 | 30,5 | 31,2 | - | - | - |

DESCRIPTION

Safety sandals with trekking design with suede upper. The shoes are equipped with a steel toe cap. The sole is made of two-component polyurethane.



ARDON
WORKWEAR
& OUTDOOR

NORMS

(EU) 2016/425

EN ISO 20345:2011 Personal protective equipment – Safety footwear

Category S1 SRA

| Categories | EN ISO 20345 | |
|--|--------------|--|
| E - energy absorption in the heel area | ✓ | |
| FO - resistance to oils and fuels | ✓ | |
| A - antistatic footwear | ✓ | |
| SRC - resistance to slipping on ceramic floor tiles with SLS and on steel floors with glycerin | | |
| WR - upper resistant to water | | |
| Safety toe cap for toe protection | ✓ | |
| P - resistance to punctures (protective insole) | | |
| SRA - slip resistance ceramic floor tiles with SLS | ✓ | |
| HRO - resistance to contact heatup to 300 °C | | |
| HI-insulation of the bottom of the shoe against heat | | |
| CI-insulation of the bottom of the shoe against the cold | | |
| Splatters of molten metal | | |
| ESD – shoe protects against electrostatic discharge and can be used on EPA premises | | |
| The shoes do not contain metal parts | | |
| - | | |
| - | | |
| - | | |

TECHNICAL SHEET



ARDON®
WORKWEAR
& OUTDOOR

| CODE | EAN | CARTON WEIGHT (KG) | UNIT WEIGHT (KG) |
|-------------|---------------|-------------------------------|-----------------------------|
| G1303/36 | 8592390082480 | 12.85 | 1.285 |
| G1303/37 | 8592390082497 | 12.87 | 1.287 |
| G1303/38 | 8592390082503 | 12.89 | 1.289 |
| G1303/39 | 8592390082510 | 12.91 | 1.291 |
| G1303/40 | 8592390082527 | 12.96 | 1.296 |
| G1303/41 | 8592390082534 | 13.10 | 1.310 |
| G1303/42 | 8592390082541 | 13.25 | 1.325 |
| G1303/43 | 8592390082558 | 13.36 | 1.336 |
| G1303/44 | 8592390082565 | 13.40 | 1.340 |
| G1303/45 | 8592390082572 | 13.41 | 1.341 |
| G1303/46 | 8592390082589 | 13.46 | 1.346 |
| G1303/47 | 8592390082596 | 13.49 | 1.349 |
| G1303/48 | 8592390082602 | 13.51 | 1.351 |



ARDON®
WORKWEAR
& OUTDOOR





ARDON®
WORKWEAR
& OUTDOOR

