




| |
|---|
| HS CODE |
| 76169990 |
| CARTON SIZE / PCS. |
| 60 x 40 x 24 cm / 50 |
| AET (UE) N°2777/10788-01/E01-01 |
| Satra Technology Europe Ltd., N° 2777, Bracetown Business Park, Clonee, Dublin, D15YN2P, Ireland |
| MODULE D FI14/14003.02 |
| SGS Fimko Oy, N°0598 Takomotie 8, 00380 HELSINKI, Finland |

| | |
|---|--|
| REF. | FA 60 004 15 |
| CE | EN 795:2012 Type B |
|  | X 1 |
| LG | 1.5 m |
| MAT. |  45 mm PES |
| R (kN) / MBS (kN) | 18 kN / 30 kN |
|  | 0.31 KG |



Nombre d'utilisateurs
Number of users
Cantidad de usuarios
Quantità di utilizzatori
Anzahl der Benutzer

R (kN) / MBS (kN)

Résistance statique (en kN) / Résistance à la rupture
Static strength / Minimum Breaking Strength
Resistencia estática (en kN) / Resistencia a la ruptura (en kN)
Resistenza statica (in kN) / Resistenza alla rottura (in kN)
Statische Festigkeit (in kN) / Bruchfestigkeit (in kN)