



ARDON®
WORKWEAR
& OUTDOOR

ARDON® TURNER S1P

SAFETY SHOES



**DEFUSE
CONTROL**



DRY AIR



REFLECTIVE

TECHNICAL SHEET

ARDON® TURNER S1P

SAFETY SHOES

ARTICLE

G3282

MATERIAL

Upper
Lining
Sole

brushed cowhide VELOR / fabric
MESH laminated breathable fabric
PU/rubber, two-component spray coating, oil resistant, anti-static,
antislip, resistant up to 300 °C

Toe cap
Plate
Insole

steel 604
steel
ANATOMIC FOAM anatomically shaped EVA foam, supports
longitudinal and transverse arches, absorbs shocks in the heel area

SIZE

UNIT

PACKAGE

Units in a carton
Units in a box

36-48
pair

10 pairs
1 pair

DIMENSIONS

Carton H x W x D
(cm)
Carton (cbm)

36-39	40-43	44-48
31.5 x 41.5 x 61.5	33.5 x 43.5 x 61.5	37 x 43.5 x 64
0,0804	0,0896	0,103

Size EUR

Insole length mm

Foot length cm

35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51
-	237	243	250	257	263	270	277	283	290	297	303	310	317	-	-	-
-	23,2	23,8	24,5	25,2	25,8	26,5	27,2	27,8	28,5	29,2	29,8	30,5	31,2	-	-	-

DESCRIPTION

Low shoes in elegant trendy design. Upper is made of brushed cowhide VELUR and fabric, reinforced in the toe, heel and ankle. The wide PU / rubber sole has SR anti-slip properties and is resistant to contact heat up to 300 ° C. The ANATOMIC FOAM insole ensures increased comfort of the shoes. For higher visibility, the shoe has a reflective strip in the heel. The shoes have a steel toe cap and an anti-puncture insole.

NORMS

(EU) 2016/425

EN ISO 20345:2022+A1:2024

Personal protective equipment – Safety footwear

Category

S1P FO SR HRO

Categories

EN ISO 20345

E - energy absorption in the heel area

✓



FO - resistance to oils and fuels

✓



A - antistatic footwear

✓



SR - resistance to slipping on ceramic floor tiles with SLS
and on steel floors with glycerin

✓



WR - upper resistant to water



Safety toe cap for toe protection

✓



P - resistance to punctures (protective insole)

✓



WPA - water penetration and absorption



HRO - resistance to contact heatup to 300 °C

✓



HI-insulation of the bottom of the shoe against heat



CI-insulation of the bottom of the shoe against the cold



Splatters of molten metal



ESD – shoe protects against electrostatic discharge and can
be used on EPA premises



The shoes do not contain metal parts



-

-

-



ARDON®
WORKWEAR
& **OUTDOOR**

CODE	EAN	CARTON WEIGHT (KG)	UNIT WEIGHT (KG)
G3282/36	8592390102997	13.95	1.395
G3282/37	8592390103000	14.30	1.430
G3282/38	8592390103017	14.45	1.445
G3282/39	8592390103024	15.00	1.500
G3282/40	8592390103031	15.75	1.575
G3282/41	8592390103048	15.95	1.595
G3282/42	8592390103055	16.20	1.620
G3282/43	8592390103062	17.00	1.700
G3282/44	8592390103079	17.55	1.755
G3282/45	8592390103086	18.00	1.800
G3282/46	8592390103093	18.30	1.830
G3282/47	8592390103109	18.70	1.870
G3282/48	8592390103116	19.10	1.910



ARDON®
WORKWEAR
& OUTDOOR





ARDON®
WORKWEAR
& OUTDOOR

