



ARDON®
WORKWEAR
& OUTDOOR

ARDON® KING S3

SAFETY SHOES



DRY AIR



REFLECTIVE



**WATER
REPELLENT**

TECHNICAL SHEET



ARDON®
WORKWEAR
& OUTDOOR

ARDON® KING S3

SAFETY SHOES

ARTICLE

G3284

MATERIAL

Upper

buffalo leather with SPLIT LEATHER design in a thickness of 1,8 - 2 mm (with hydrophobic treatment)

Lining

laminated breathable fabric MESH

Sole

PU/PU, two-component spray coating, oil resistant, anti-static, antislip

Toe cap

Steel 459

Plate

Steel

Insole

BASIC

SIZE

36-48

UNIT

pair

PACKAGE

Units in a carton

10 pairs

Units in a box

1 pair

DIMENSIONS

Carton H x W x D

36-43
36 x 49 x 65

44-48
37 x 49,5 x 69

(cm)

Carton (cbm)

0,115

0,126

Size EUR

35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51
----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----

Insole length mm

-	241	247	255	262	270	276	282	288	298	304	309	315	320	-	-	-
---	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	---	---	---

Foot length cm

-	23,1	23,7	24,5	25,2	26,0	26,6	27,2	27,8	28,8	29,4	29,9	30,5	31,0	-	-	-
---	------	------	------	------	------	------	------	------	------	------	------	------	------	---	---	---

DESCRIPTION

Ardon safety ankle shoes with leather upper (with hydrophobic treatment) , with reflective elements.
Sole made of double density PU / PU material.















NORMS

(EU) 2016/425

EN ISO 20345:2022 Personal protective equipment –Safety footwear

Category S3 SR FO

EN ISO 20345:2022/A1:2024

Categories	EN ISO 20345	
E - energy absorption in the heel area	✓	
FO - resistance to oils and fuels	✓	
A - antistatic footwear	✓	
SR - resistance to slipping on ceramic floor tiles with SLS and on steel floors with glycerin	✓	
WR - upper resistant to water	✓	
Safety toe cap for toe protection	✓	
P - resistance to punctures (protective insole)	✓	
WPA - water penetration and absorption	✓	
HRO - resistance to contact heatup to 300 °C		
HI-insulation of the bottom of the shoe against heat		
CI-insulation of the bottom of the shoe against the cold		
Splatters of molten metal		
ESD – shoe protects against electrostatic discharge and can be used on EPA premises		
The shoes do not contain metal parts		
-		
-		
-		

**ARDON®****WORKWEAR
& OUTDOOR**

CODE	EAN	CARTON WEIGHT (KG)	UNIT WEIGHT (KG)
G3284/36	8592390107954	16,80	1,680
G3284/37	8592390107961	17,00	1,700
G3284/38	8592390107978	17,20	1,720
G3284/39	8592390107985	17,60	1,760
G3284/40	8592390107992	18,00	1,800
G3284/41	8592390108005	18,50	1,850
G3284/42	8592390108012	19,20	1,920
G3284/43	8592390108029	19,60	1,960
G3284/44	8592390108036	20,10	2,010
G3284/45	8592390108043	20,60	2,060
G3284/46	8592390108050	21,10	2,110
G3284/47	8592390108067	21,50	2,150
G3284/48	8592390108074	22,20	2,220



ARDON®
WORKWEAR
& OUTDOOR





ARDON®
WORKWEAR
& **OUTDOOR**



TECHNICAL SHEET