



ARDON®
WORKWEAR
& OUTDOOR

ARDON® KINGLOW S3

SAFETY SHOES



DRY AIR



REFLECTIVE



WATER
REPELLENT

TECHNICAL SHEET



ARDON®
WORKWEAR
& OUTDOOR

ARDON® KINGLOW S3

SAFETY SHOES

ARTICLE

G3285

MATERIAL

Upper

buffalo leather with SPLIT LEATHER design in a thickness of 1,8 - 2 mm (with hydrophobic treatment)

Lining

laminated breathable fabric MESH

Sole

PU/PU, two-component spray coating, oil resistant, anti-static, antislip

Toe cap

Steel 459

Plate

Steel

Insole

BASIC

SIZE

36-48

UNIT

pair

PACKAGE

Units in a carton

10 pairs

Units in a box

1 pair

DIMENSIONS

Carton H x W x D
(cm)

36-43
36 x 49 x 65

44-48
37 x 49,5 x 69

Carton (cbm)

0,115

0,126

Size EUR

35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51
----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----

Insole length mm

-	241	247	255	262	270	276	282	288	298	304	309	315	320	-	-	-
---	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	---	---	---

Foot length cm

-	23,6	24,2	25,0	25,7	26,5	27,1	27,7	28,3	29,3	29,9	30,4	31,0	31,5	-	-	-
---	------	------	------	------	------	------	------	------	------	------	------	------	------	---	---	---

DESCRIPTION

Ardon safety low shoes with leather upper (with hydrophobic treatment) , with reflective elements.
Sole made of double density PU / PU material.















NORMS

(EU) 2016/425

EN ISO 20345:2022 Personal protective equipment –Safety footwear

Category S3 SR FO

EN ISO 20345:2022/A1:2024

Categories	EN ISO 20345	
E - energy absorption in the heel area	✓	
FO - resistance to oils and fuels	✓	
A - antistatic footwear	✓	
SR - resistance to slipping on ceramic floor tiles with SLS and on steel floors with glycerin	✓	
WR - upper resistant to water	✓	
Safety toe cap for toe protection	✓	
P - resistance to punctures (protective insole)	✓	
WPA - water penetration and absorption	✓	
HRO - resistance to contact heatup to 300 °C		
HI-insulation of the bottom of the shoe against heat		
CI-insulation of the bottom of the shoe against the cold		
Splatters of molten metal		
ESD – shoe protects against electrostatic discharge and can be used on EPA premises		
The shoes do not contain metal parts		
-		
-		
-		



ARDON®
WORKWEAR
& OUTDOOR

CODE	EAN	CARTON WEIGHT (KG)	UNIT WEIGHT (KG)
G3285/36	8592390108081	16,80	1,680
G3285/37	8592390108098	17,00	1,700
G3285/38	8592390108104	17,20	1,720
G3285/39	8592390108111	17,60	1,760
G3285/40	8592390108128	18,00	1,800
G3285/41	8592390108135	18,50	1,850
G3285/42	8592390108142	19,20	1,920
G3285/43	8592390108159	19,60	1,960
G3285/44	8592390108166	20,10	2,010
G3285/45	8592390108173	20,60	2,060
G3285/46	8592390108180	21,10	2,110
G3285/47	8592390108197	21,50	2,150
G3285/48	8592390108203	22,20	2,220



ARDON®
WORKWEAR
& OUTDOOR





ARDON®
WORKWEAR
& **OUTDOOR**



TECHNICAL SHEET