



ARDON®
WORKWEAR
& OUTDOOR

ARDON® KINGSAN S1

SAFETY SHOES



DRY AIR



REFLECTIVE



ZIPPER

TECHNICAL SHEET



ARDON®
WORKWEAR
& OUTDOOR

ARDON®KINGSAN S1

SAFETY SHOES

ARTICLE

G3286

MATERIAL

Upper

buffalo leather with SPLIT LEATHER design in a thickness of 1,8 - 2 mm

Lining

laminated breathable fabric MESH

Sole

PU/PU, two-component spray coating, oil resistant, anti-static, antislip

Toe cap

Steel 459

Plate

Insole

BASIC

SIZE

36-48

UNIT

pair

PACKAGE

Units in a carton

10 pairs

Units in a box

1 pair

DIMENSIONS

Carton H x W x D

36-43
36 x 49 x 65

44-48
37 x 49,5 x 69

(cm)

Carton (cbm)

0,115

0,126

Size EUR

35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51
----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----

Insole length mm

-	241	247	255	262	270	276	282	288	298	304	309	315	320	-	-	-
---	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	---	---	---

Foot length cm

-	23,6	24,2	25,0	25,7	26,5	27,1	27,7	28,3	29,3	29,9	30,4	31,0	31,5	-	-	-
---	------	------	------	------	------	------	------	------	------	------	------	------	------	---	---	---

DESCRIPTION

Sandal with leather upper, fastening with Velcro strap. Safety is ensured by a steel toe cap. Sole made of double density PU /PU material.















NORMS

(EU) 2016/425

EN ISO 20345:2022 Personal protective equipment –Safety footwear

EN ISO 20345:2022/A1:2021

Category S1 SR FO

Categories	EN ISO 20345	
E - energy absorption in the heel area	✓	
FO - resistance to oils and fuels	✓	
A - antistatic footwear	✓	
SR - resistance to slipping on ceramic floor tiles with SLS and on steel floors with glycerin	✓	
WR - upper resistant to water		
Safety toe cap for toe protection	✓	
P - resistance to punctures (protective insole)		
WPA - water penetration and absorption		
HRO - resistance to contact heatup to 300 °C		
HI-insulation of the bottom of the shoe against heat		
CI-insulation of the bottom of the shoe against the cold		
Splatters of molten metal		
ESD – shoe protects against electrostatic discharge and can be used on EPA premises		
The shoes do not contain metal parts		
-		
-		
-		



ARDON®
WORKWEAR
& OUTDOOR

CODE	EAN	CARTON WEIGHT (KG)	UNIT WEIGHT (KG)
G3286/36	8592390108210	14,40	1,440
G3286/37	8592390108227	14,60	1,460
G3286/38	8592390108234	14,80	1,480
G3286/39	8592390108241	15,20	1,520
G3286/40	8592390108258	15,70	1,570
G3286/41	8592390108265	15,90	1,590
G3286/42	8592390108272	16,10	1,610
G3286/43	8592390108289	17,40	1,740
G3286/44	8592390108296	17,80	1,780
G3286/45	8592390108302	18,20	1,820
G3286/46	8592390108319	18,60	1,860
G3286/47	8592390108326	18,90	1,890
G3286/48	8592390108333	19,20	1,920



ARDON®
WORKWEAR
& OUTDOOR





ARDON®
WORKWEAR
& OUTDOOR

