



ARDON®
WORKWEAR
& OUTDOOR

ARDON® FLYKER BLUE S1PS

SAFETY SHOES



DRY AIR



DEFUSE
CONTROL



NONMETALLIC

3DKNIT

3D KNIT



FLAT ANTI-SLIP

TECHNICAL SHEET



ARDON®
WORKWEAR
& OUTDOOR

ARDON® FLYKER BLUE S1PS

SAFETY SHOES

ARTICLE G3324

MATERIAL

Upper 3D KNIT type knitted two-layer fabric
 Lining MESH laminated breathable fabric
 Sole Phylon/rubber, oil resistant, antistatic, anti-slip, glued technology

Toe cap composite 459
 Plate kevlar
 Insole ANATOMIC FOAM anatomically shaped EVA foam

SIZE

36-47

UNIT

pair

PACKAGE

Units in a carton 10 pairs
 Units in a box 1 pair

DIMENSIONS

	36-42	43-47
Carton H x W x D (cm)	32.5 x 39.5 x 58	36.5 x 41.5 x 63
Carton (cbm)	0,0745	0,095

Size EUR	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51
Insole length mm	-	232	239	246	253	260	267	273	280	287	293	300	307	-	-	-	-
Foot length cm	-	22,7	23,4	24,1	24,8	25,5	26,2	26,8	27,5	28,2	28,8	29,5	30,2	-	-	-	-

DESCRIPTION

The street-cut safety shoe, high quality upper is made of flyknit material, an extremely durable fabric that is also very breathable. The textile mesh lining has excellent properties against abrasion and allows for good ventilation while at the same time preventing excessive sweating of the feet. The shoes are equipped with a composite toe and a flexible Kevlar insole against puncture. The stable flat sole made of rubber provides the highest level of anti-slip properties.

TECHNICAL SHEET



ARDON®
WORKWEAR
& OUTDOOR

NORMS

(EU) 2016/425

EN ISO 20345:2022+A1:2024

Personal protective equipment – Safety footwear

Category

S1 PS FO SR

Categories	EN ISO 20345	
E - energy absorption in the heel area	✓	
FO - resistance to oils and fuels	✓	
A - antistatic footwear	✓	
SR - resistance to slipping on ceramic floor tiles with SLS and on steel floors with glycerin	✓	
WPA – water penetration and absorption		
Safety toe cap for toe protection	✓	
P - resistance to punctures (protective insole)	✓	
The shoes do not contain metal parts	✓	
HRO - resistance to contact heat up to 300 °C		
HI-insulation of the bottom of the shoe against heat		
CI-insulation of the bottom of the shoe against the cold		
Splatters of molten metal		
ESD – shoe protects against electrostatic discharge and can be used on EPA premises		
-		
-		
-		

TECHNICAL SHEET



ARDON®
WORKWEAR
& OUTDOOR

CODE	EAN	CARTON WEIGHT (KG)	UNIT WEIGHT (KG)
G3324/36	8592390124159	7.50	0.750
G3324/37	8592390124166	7.70	0.770
G3324/38	8592390124173	8.00	0.800
G3324/39	8592390124180	8.40	0.840
G3324/40	8592390124197	8.70	0.870
G3324/41	8592390124203	9.00	0.900
G3324/42	8592390124210	9.50	0.950
G3324/43	8592390124227	10.40	1.040
G3324/44	8592390124234	10.70	1.070
G3324/45	8592390124241	11.00	1.100
G3324/46	8592390124258	11.40	1.140
G3324/47	8592390124265	11.80	1.180



ARDON®
WORKWEAR
& OUTDOOR



TECHNICAL SHEET



ARDON®
WORKWEAR
& OUTDOOR

