



ARDON®
WORKWEAR
& OUTDOOR

ARDON® SPARKLE S3

SAFETY SHOES



DEFUSE
CONTROL



DRY AIR



WATER
REPELLENT



REFLECTIVE

TECHNICAL SHEET



ARDON®
WORKWEAR
& OUTDOOR

ARDON® SPARKLE S3

SAFETY SHOES

ARTICLE G3384

MATERIAL

Upper Full grain cowhide 1.8 – 2 mm thick, hydrophobic treatment
Lining MESH-type laminated breathable fabric
Sole PU/rubber, direct injection
Toe cap 604 composite
Plate Kevlar
Insole ANATOMIC FOAM – anatomically shaped from EVA foam

SIZE 39-48

UNIT pair

PACKAGE

Units in a carton 10 pairs
Units in a box 1 pair

DIMENSIONS

	39	40-43	44-48
Carton H x W x D (cm)	31.5 x 45.5 x 61.5	33.5 x 47.5 x 61.5	37 x 49.5 x 64
Carton (cbm)	0,0881	0,0979	0,1172

Size EUR	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51
Insole length mm	-	-	-	-	257	264	270	277	284	290	297	304	310	317	-	-	-
Foot length cm	-	-	-	-	25,2	25,9	26,5	27,2	27,9	28,5	29,2	29,9	30,5	31,2	-	-	-

DESCRIPTION

Safety shoes with upper made of high-quality full-grain leather, leather tongue and ankle area, with hydrophobic treatment, with composite toe cap and Kevlar insole. The sole made of PU/rubber material has anti-slip SRC properties, is resistant to contact heat up to 300°C, provides insulation against heat and cold.

NORMS















(EU) 2016/425

EN ISO 20345:2011

Personal protective equipment - Safety footwear

Category:

S3 HRO SRC HI CI

Categories	EN ISO 20345	
E - energy absorption in the heel area	✓	
FO - resistance to oils and fuels	✓	
A - antistatic footwear	✓	
SRC - resistance to slipping on ceramic floor tiles with SLS and on steel floors with glycerin	✓	
WR - upper resistant to water	✓	
Safety toe cap for toe protection	✓	
P - resistance to punctures (protective insole)	✓	
SRA - slip resistance ceramic floor tiles with SLS		
HRO - resistance to contact heatup to 300 °C	✓	
insulation of the bottom of the shoe against heat	✓	
insulation of the bottom of the shoe against the cold	✓	
Splatters of molten metal		
ESD – shoe protects against electrostatic discharge and can be used on EPA premises		
The shoes do not contain metal parts		
-		
-		
-		



ARDON®
WORKWEAR
& OUTDOOR

CODE	EAN	CARTON WEIGHT (KG)	UNIT WEIGHT (KG)
G3384/39	8592390162908	16.00	1.600
G3384/40	8592390162915	16.75	1.675
G3384/41	8592390162922	17.00	1.700
G3384/42	8592390162939	17.50	1.750
G3384/43	8592390162946	18.55	1.855
G3384/44	8592390162953	19.45	1.945
G3384/45	8592390162960	20.20	2.020
G3384/46	8592390162977	20.35	2.035
G3384/47	8592390162984	21.20	2.120
G3384/48	8592390162991	21.50	2.150



ARDON®
WORKWEAR
& OUTDOOR





ARDON®

**WORKWEAR
& OUTDOOR**



TECHNICAL SHEET

© ARDON s.r.o. / ALL RIGHTS RESERVED

ARDON s.r.o. tř. Kosmonautů 1221/2a, Olomouc www.ardon.cz