



ARDON®
WORKWEAR
& OUTDOOR

ARDON® SPARKLELOW S3

SAFETY SHOES



DEFUSE
CONTROL



DRY AIR



WATER
REPELLENT



REFLECTIVE

TECHNICAL SHEET



ARDON®
WORKWEAR
& **OUTDOOR**

ARDON® SPARKLELOW S3

SAFETY SHOES

ARTICLE

G3385

MATERIAL

Upper Full grain cowhide 1.8 – 2 mm thick, hydrophobic treatment
Lining MESH-type laminated breathable fabric
Sole PU/rubber, direct injection
Toe cap 604 composite
Plate Kevlar
Insole ANATOMIC FOAM – anatomically shaped from EVA foam

SIZE

37-48

UNIT

pair

PACKAGE

Units in a carton 10 pairs
Units in a box 1 pair

DIMENSIONS

	37-39	40-43	44-48
Carton H x W x D (cm)	31.5 x 41.5 x 61.5	33.5 x 43.5 x 61.5	37 x 43.5 x 64
Carton (cbm)	0,0804	0,0896	0,103

Size EUR	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51
Insole length mm	-	-	244	250	257	264	270	277	284	290	297	304	310	317	-	-	-
Foot length cm	-	-	23,9	24,5	25,2	25,9	26,5	27,2	27,9	28,5	29,2	29,9	30,5	31,2	-	-	-

DESCRIPTION

Safety shoes with upper made of high-quality full-grain leather, leather tongue and ankle area, with hydrophobic treatment, with composite toe cap and Kevlar insole. The sole made of PU/rubber material has anti-slip SRC properties, is resistant to contact heat up to 300°C, provides insulation against heat and cold.

TECHNICAL SHEET

NORMS















(EU) 2016/425

EN ISO 20345:2011

Personal protective equipment - Safety footwear

Category:

S3 HRO SRC HI CI

Categories	EN ISO 20345	
E - energy absorption in the heel area	✓	
FO - resistance to oils and fuels	✓	
A - antistatic footwear	✓	
SRC - resistance to slipping on ceramic floor tiles with SLS and on steel floors with glycerin	✓	
WR - upper resistant to water	✓	
Safety toe cap for toe protection	✓	
P - resistance to punctures (protective insole)	✓	
SRA - slip resistance ceramic floor tiles with SLS		
HRO - resistance to contact heatup to 300 °C	✓	
insulation of the bottom of the shoe against heat	✓	
insulation of the bottom of the shoe against the cold	✓	
Splatters of molten metal		
ESD – shoe protects against electrostatic discharge and can be used on EPA premises		
The shoes do not contain metal parts		
-		
-		
-		



ARDON®
WORKWEAR
& **OUTDOOR**

CODE	EAN	CARTON WEIGHT (KG)	UNIT WEIGHT (KG)
G3385/37	8592390163004	14.00	1.400
G3385/38	8592390163011	15.00	1.500
G3385/39	8592390163028	15.50	1.550
G3385/40	8592390163035	15.80	1.580
G3385/41	8592390163042	16.00	1.600
G3385/42	8592390163059	17.00	1.700
G3385/43	8592390163066	18.00	1.800
G3385/44	8592390163073	18.50	1.850
G3385/45	8592390163080	19.00	1.900
G3385/46	8592390163097	19.50	1.950
G3385/47	8592390163103	20.00	2.000
G3385/48	8592390163110	21.00	2.210



ARDON®
WORKWEAR
& OUTDOOR





ARDON®

**WORKWEAR
& OUTDOOR**



TECHNICAL SHEET

© ARDON s.r.o. / ALL RIGHTS RESERVED

ARDON s.r.o. tř. Kosmonautů 1221/2a, Olomouc www.ardon.cz