



ARDON®
WORKWEAR
& OUTDOOR

ARDON® XLIGHT YELLOW ESD S1P

SAFETY SHOES



DEFUSE
CONTROL



DRY AIR



NONMETALLIC



REFLECTIVE



ESD

TECHNICAL SHEET



ARDON®
WORKWEAR
& **OUTDOOR**

ARDON® XLIGHT YELLOW ESD S1P

SAFETY SHOES

ARTICLE

G3396

MATERIAL

Upper: Breathable fabric / TPU
Lining: Laminated breathable fabric MESH
Sole: Phylon/rubber, glued technology
Toe cap: Nano composite
Plate: FENGTA Ultralight kevlar
Insole: ANATOMIC FOAM – anatomically shaped from EVA foam

SIZE

36-48

UNIT

pair

PACKAGE

Units in a carton: 10 pairs
Units in a box: 1 pair

DIMENSIONS

	36-40	41-44	45-48	-
Carton H x W x D (cm)	32,5 x 41,5 x 54,5	34 x 44,5 x 57	36,5 x 48,5 x 62	-
Carton (cbm)	0,074	0,086	0,110	-

Size EUR	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51
Insole length mm	-	239	246	253	259	266	273	280	286	293	300	307	313	320	-	-	-
Foot length cm	-	23,4	24,1	24,8	25,4	26,1	26,8	27,5	28,1	28,8	29,5	30,2	30,8	31,5	-	-	-

DESCRIPTION

Ultralight safety shoe with a sporty cut, with a nano composite toe cap and an ultralight Kevlar soleplate, with an upper made of gray breathable fabric with a print.

TECHNICAL SHEET

NORMS

(EU) 2016/425

EN ISO 20345:2011















EN61340-5-1:2016

Personal protective equipment - Safety footwear
Protection of electronic devices from electrostatic
phenomena - General requirements

Category: S1P SRC ESD

Categories

EN ISO 20345

E - energy absorption in the heel area	✓	
FO - resistance to oils and fuels	✓	
A - antistatic footwear	✓	
SRC - resistance to slipping on ceramic floor tiles with SLS and on steel floors with glycerin	✓	
WR - upper resistant to water		
Safety toe cap for toe protection	✓	
P - resistance to punctures (protective insole)	✓	
SRA - slip resistance ceramic floor tiles with SLS		
HRO - resistance to contact heatup to 300 °C		
insulation of the bottom of the shoe against heat		
insulation of the bottom of the shoe against the cold		
Splatters of molten metal		
ESD – shoe protects against electrostatic discharge and can be used on EPA premises	✓	
The shoes do not contain metal parts	✓	
-		
-		
-		



ARDON®
WORKWEAR
& OUTDOOR

CODE	EAN	CARTON WEIGHT (KG)	UNIT WEIGHT (KG)
G3396/36	8592390165435	9,55	0,955
G3396/37	8592390165442	10,15	1,015
G3396/38	8592390165459	10,25	1,025
G3396/39	8592390165466	10,55	1,055
G3396/40	8592390165473	10,80	1,080
G3396/41	8592390165480	11,00	1,100
G3396/42	8592390165497	11,20	1,120
G3396/43	8592390165503	11,35	1,135
G3396/44	8592390165510	11,55	1,155
G3396/45	8592390165527	11,70	1,170
G3396/46	8592390165534	11,85	1,185
G3396/47	8592390165541	12,00	1,200
G3396/48	8592390165558	12,15	1,215



ARDON®
WORKWEAR
& OUTDOOR





ARDON®
WORKWEAR
& OUTDOOR

