



ARDON®
WORKWEAR
& OUTDOOR

ARDON® Winfine

ALLROUND HANDLING IN DRY ENVIRONMENT WITH PROTECTION AGAINST VERY LOW AND HIGH TEMPERATURES WITH HIGH MECHANICAL PROTECTION



TECHNICAL DATA



EN 388: 2016



EN 407: 2004



EN 511: 2006



ARDON®
WORKWEAR
& OUTDOOR

ARDON® Winfine

ALLROUND HANDLING IN DRY ENVIRONMENT WITH PROTECTION AGAINST VERY LOW AND HIGH TEMPERATURES WITH HIGH MECHANICAL PROTECTION

CODE A9114

MATERIAL

Lining 7G acrylic (inner) + 13G polyester (outer)
 Coating latex foam with sand pattern
 Thickness 3,4 mm (in palm)

SIZE(S) 6 / XS – 12 / 3XL

UNIT pair

PACKING


Units in carton 60 pairs
 Units in polybag 12 pairs
 Retail packaging also with a sales label

DIMENSIONS

	5	6	7	8	9	10	11	12
Carton H x W x D (cm)	-	58x28x25	58x28x25	58x28x25	58x28x25	58x28x25	58x28x25	58x28x25
Carton (cbm)	-	0,0406	0,0406	0,0406	0,0406	0,0406	0,0406	0,0406

WEIGHT

	5	6	7	8	9	10	11	12
Carton (kg)	-	5,5	5,600	5,700	5,900	6,300	6,800	7,200
Unit (g)	-	90,0	93,33	95,00	98,30	105,0	113,3	120,0



Size chart (cm)

	5	6	7	8	9	10	11	12
Total length (A)	-	23	23,5	24,0	25,0	26,0	27,0	28,0
Cuff length (B)	-	7,5	7,50	7,50	8,00	8,00	8,50	8,70
Cuff width (C)	-	7	7,30	7,50	8,00	8,50	9,00	9,20
Palm width (D)	-	9	9,50	10,0	11,0	11,5	12,0	12,5

Tolerance (A) ± 0,50 (cm)

Tolerance (B) ± 0,30 (cm)

Tolerance (C) ± 0,30 (cm)

Tolerance (D) ± 0,30 (cm)

DESCRIPTION

Winter gloves with double knit dipped in latex foam with sand pattern (sand-like finish).



ARDON®
WORKWEAR
& OUTDOOR

STANDARDS

(EU) 2016/425

EN ISO 21420:2020 Protective gloves – general requirements and test methods

EN 388:2016 + A1:2018 Protective gloves against mechanical risks



PROTECTION LEVELS

MECHANICAL RISKS

abrasion resistance
cut resistance
tearing resistance
puncture resistance
cut resistance acc. to ISO

LVL

2
2
2
2
B

score

500 – 2.000
2,5 – 5,0
25 – 50
60 – 100
5 – 10

unit

cycles
index
N
N
N

EN 407:2004

Protective gloves against heat or flame



PROTECTION LEVELS

THERMAL RISKS

resistance to burning
resistance to contact heat
resistance to convectional heat
resistance to radiant heat
resistance to small drops of molten metals
resistance to large drops of molten metals

LVL

X
2
X
X
X
X

score

not measured
250°C for 15s
not measured
not measured
not measured
not measured

EN 511:2006

Protective gloves against cold



PROTECTION LEVELS

COLD RISKS

resistance to convection cold
resistance to contact cold
water permeability

LVL

X
2
X

not measured
not measured
not measured



ARDON®
WORKWEAR
& OUTDOOR

SPECIAL FEATURES

- multifunctional so-called all-round gloves:
 - for work in dry environment (for example with water-based bulk mixtures, especially in building / mortar, paints, etc.)
 - high protection against cold and heat (composition of two layers of functional materials and a thick layer of latex better insulate against external influences and keep the body warm)
 - protection against heat up to 150°C*
 - latex with sand pattern („sand-like finish“) serves as a barrier against liquids and palm injuries
- wide size range 6 – 12 (XS – 3XL) with each size with its own specific hem color
- ARDON® design:
 - mandatory information on inner label
 - reflective manufacturer's logo
 - each pair is also available in retail-ready packaging

* - according to certification up to 250°C for 15 seconds, but we generally do not recommend exposure to temperatures higher than 150°C, during which latex secondary vulcanizes and heats up

TECHNICAL DATA

Retail packaging (with sales label)

	EAN	HEM COLOR
A9114/06-SPE	8592390146687	purple
A9114/07-SPE	8592390124517	red
A9114/08-SPE	8592390112446	blue
A9114/09-SPE	8592390112453	brown
A9114/10-SPE	8592390112460	black
A9114/11-SPE	8592390124524	green
A9114/12-SPE	8592390010445	yellow

Basic packing (without a sales label)

	EAN	HEM COLOR
A9114/08	8592390359384	blue
A9114/09	8592390359414	brown
A9114/10	8592390359445	black
A9114/11	8592390358783	green



ARDON®
WORKWEAR
& **OUTDOOR**

TECHNICAL DATA

