



**ARDON®**  
**WORKWEAR**  
& **OUTDOOR**

## **ARDON® AS-5**

INDUSTRIAL SAFETY HELMET



TECHNICAL DATA SHEET



**ARDON®**  
**WORKWEAR**  
& **OUTDOOR**

## ARDON® AS-5

INDUSTRIAL SAFETY HELMET

**ARTIKL No.**

**D1004**

**MATERIAL**

HDPE (high density polyethylen)

**COLOURS**

white, green, orange, blue, red, yellow

**SIZE**

53 – 63 cm

### DESCRIPTION

This protective helmet offers ultimate comfort, and provides excellent head protection. Very lightweight, strong, and comfortable. Vntilation holes, smooth size adjustment is achieved through a adjustable wheel in the range of 53 to 63 cm. Extremely resistant to temperatures from -20°C to +50°C. An excellent choice for protection against falling objects, impacts, and bumps. Maximum lifespan is 5 years from the date of manufacture.

Compatible with:

- Helmet mounted earmuffs ARDON®EARZONE X801
- Chin-strap AS-5-2
- Sweat band AS-5-3
- 6 point webbing harness AS-5-4

## STANDARDS

This personal protective equipment is in conformity with these harmonized European Standards:

**EN 397:2012+A1:2012:** Industrial safety helmets

Certified by notified body no. 1024 Research Institute Labour and Social Affairs, v. v. i., (Jeruzalémská 1283/9, 110 00, Praha 1, Czech republic), Certificate number 1024/E-005/2025, dated 24<sup>th</sup> of March 2025

Industrial safety helmets ARDON<sup>®</sup>AS-5 meet the requirements of the Regulation (EU) 2016/425 on personal protective equipment and requirements of the Regulation (EU) 2023/998 on general product safety.

<b>UNITS IN A CARTON</b>	20 pcs
<b>CARTON WEIGHT</b>	10 kg
<b>CARTON SIZE</b>	0,142 m <sup>3</sup>
<b>UNIT PACKAGING</b>	1 pc

For full protection, this product must be adjusted to fit the user's head size. You can adjust the size by adjusting the fastening strap at the back of the helmet. In case of dirt, clean the product with lukewarm water and a neutral soap or a small amount of mild detergent, then rinse thoroughly and let it dry naturally in the shade. The helmet must not be dried in a dryer or near a radiator under any circumstances. Do not use paints, solvents, chemicals, adhesives, gasoline, or similar substances. These substances may destroy the impact resistance and other protective properties of the helmet without being apparent or readily detectable by the user. When not in use, it is best to store the helmet at a temperature between 10°C and 25°C, protected from direct sunlight and away from heat sources. Before each use, inspect the helmet thoroughly to ensure it is not cracked, cut, or otherwise damaged.