



ARDON®
WORKWEAR
& OUTDOOR

ARDON®ENERDIG S3S ESD

SAFETY SHOES



DRY AIR



NONMETALLIC



REFLECTIVE



DEFUSE
CONTROL



WATER
REPELLENT

TECHNICAL SHEET

ARDON® ENERDIG S3S ESD

SAFETY SHOES

ARTICLE

G3442

MATERIAL

Upper
Lining
Sole

Recycled MICROFIBER + recycled mesh
Recycled laminated breathable fabric MESH
MD/TPU/rubber, cemented technology

Toe cap
Plate
Insole

Composite 885
Recycled kevlar
Anatomic foam

SIZE

UNIT

PACKAGE

Units in a carton
Units in a box

36-48
pair

10 pairs
1 pair

DIMENSIONS

Carton H x W x D
(cm)
Carton (cbm)

36-43
63 x 48,5 x 34

43-48
63 x 52,5 x 37

0,104

0,122

Size EUR	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51
Insole length mm	-	238	244	251	258	264	271	278	284	291	298	304	311	318	-	-	-
Foot length cm	-	23,3	23,9	24,6	25,3	25,9	26,6	27,3	27,9	28,6	29,3	29,9	30,6	31,3	-	-	-

DESCRIPTION

Safety shoe in a sporty design, featuring a composite toe cap and a kevlar midsole. The water-resistant upper is made of mesh textile and microfiber, with a reinforced toe protected by a PU scuff guard. The outsole, made from a combination of MD/rubber/TPU materials, provides a soft step and SR slip resistance. The main upper materials are made from recycled materials.

NORMS














(EU) 2016/425

EN ISO 20345:2022

Personal protective equipment – safety footwear

Category

S3S SR FO ESD

Categories	EN ISO 20345	
E - energy absorption in the heel area	✓	
FO - resistance to oils and fuels	✓	
A - antistatic footwear	✓	
SR - resistance to slipping on ceramic floor tiles with SLS and on steel floors with glycerin	✓	
The shoes do not contain metal parts	✓	
Safety toe cap for toe protection	✓	
P - resistance to punctures (protective insole)	✓	
WPA – water penetration and absorption	✓	
HRO - resistance to contact heatup to 300 °C		
HI-insulation of the bottom of the shoe against heat		
CI-insulation of the bottom of the shoe against the cold		
Splatters of molten metal		
ESD – shoe protects against electrostatic discharge and can be used on EPA premises	✓	
-		
-		
-		



ARDON®
WORKWEAR
& OUTDOOR

CODE	EAN	CARTON WEIGHT (KG)	UNIT WEIGHT (KG)
G3442/36	8592390379566	11.80	1.180
G3442/37	8592390379573	12.10	1.210
G3442/38	8592390379580	12.30	1.230
G3442/39	8592390379597	12.60	1.260
G3442/40	8592390379603	12.80	1.280
G3442/41	8592390379610	13.30	1.330
G3442/42	8592390379627	13.40	1.340
G3442/43	8592390379634	13.70	1.370
G3442/44	8592390379641	14.20	1.420
G3442/45	8592390379658	15.00	1.500
G3442/46	8592390379665	15.10	1.510
G3442/47	8592390379672	15.30	1.530



ARDON®
WORKWEAR
& OUTDOOR





ARDON®
WORKWEAR
& OUTDOOR

