



ARDON®
WORKWEAR
& OUTDOOR

ARDON®S-4

SHIELD WITH CHIN GUARD



TECHNICAL DATA SHEET



ARDON[®]
WORKWEAR
& OUTDOOR

ARDON[®]S-4

SHIELD WITH CHIN GUARD

ARTIKL No. E4305

MATERIAL

polycarbonate

LABELING

AR UL 1,2 ET HMT 1 9

VISOR

clean



DESCRIPTION

The S4 Face Shield with chin protection is designed for the most demanding work operations. It is engineered to provide comprehensive facial protection where standard shields fall short. Its key advantage is an extended design with an integrated chin guard, ensuring a complete barrier not only for the eyes and face but also for the lower jaw and neck. This area is often overlooked, even though it is one of the most vulnerable zones during liquid splashes or flying particles. The shield features an excellent anti-scratch and anti-fog coating.

Applications: heavy industry, laboratories, chemical industry, construction.

TECHNICAL DATA SHEET



ARDON[®]
WORKWEAR
& OUTDOOR




STANDARDS

The protective eyewear complies with the requirements of Regulation (EU) 2016/425 of the European Parliament and of the Council on personal protective equipment, and Regulation (EU) 2023/998 on general product safety.

EN ISO 16321-1:2022: Eye and face protection for occupational use
Part 1: General requirements

Certification was carried out by Notified Body No. 0598 (SGS Fimko Oy, Takomotie 8, FI-00380 Helsinki, Finland), certificate No. 0598/PPE/25/5666, dated 03 December 2025.

Visor clean , UV 380, AR UL 1,2 ET HMT 1 9

Filter type	UL	UV filter
Shade number	1,2	Clean visor
Optical class	1	Suitable for continuous wear
Mechanical strength	HMT	Resistant to impacts from heavy objects at extreme temperatures
	ET	Resistance to impacts from high-speed particles with high energy at extreme temperatures
Anti-fog visor	✓	
Preprotection against liquids	✓	
Protection against molten metal and hot solid particles	✓	
Anti-fog visor	✓	
Scratch-resistant coating	✓	
UV protective layer	✓	



ARDON®

**WORKWEAR
& OUTDOOR**

QUANTITY PER CARTON:	50 pcs
QUANTITY PER POLYBAG:	1 pcs
CARTON WEIGHT:	7,5 kg
CARTON VOLUME:	0,06 m ³
INNER PACKAGING:	1 pcs

The product must be stored in its packaging in a dry, clean place, away from direct sunlight, at temperatures between 5°C and +55°C, with relative humidity up to 90%, and away from sources of gasoline fumes and solvents. Cleaning is recommended after each use. Clean at room temperature using a clean cloth lightly moistened with a mild solution of water and detergent. Do not use hot water, gasoline, degreasing agents, organic solvents, or abrasive cleaning agents for cleaning.



TECHNICAL DATA SHEET