



Helmet Visor for ARDON® PrimeGuard and ARDON® HighGuard



TECHNICAL DATA



ARDON®
WORKWEAR
& **OUTDOOR**

Helmet visor ARDON®

Helmet Visor for ARDON® PrimeGuard and ARDON® HighGuard

ARTICLE NO.

D1066 (clean)
D1066 (smoke)

Material

Polycarbonate

Visor marking

Clean	C 16321 1-M
Smoke	UL2C 16321 1-M



DESCRIPTION

The replacement visor is a highly functional piece of personal eye protection designed for demanding work environments where there is an immediate risk of eye injury. It provides reliable protection for the eyes and upper face against high-speed flying particles. The visor effectively deflects flying sawdust, wood chips, material splinters, dust, small gravel, and other mechanical debris.

It is ideal for use in construction, forestry, woodworking, metalworking, and assembly applications.

The visor is compatible only with the ARDON® HighGuard (D1051) and ARDON® PrimeGuard (D1054) safety helmets.

The visor does not protect against chemicals, extreme heat, flames, gases, vapours, or infrared radiation. The smoke visor protects the user's eyes from harmful sunlight and ultraviolet (UV) radiation. It significantly reduces glare when working in direct sunlight, helping to prevent eye fatigue, loss of concentration, and long-term vision damage during outdoor work.

STANDARDS

This personal protective equipment complies with the requirements of the following harmonized standard:

EN ISO 16321-1:2022/A1:2025: **Eye and face protection for occupational use -
Part 1: General requirements**

The safety glasses comply with the requirements of Regulation (EU) 2016/425 of the European Parliament and of the Council on personal protective equipment and Regulation (EU) 2023/998 of the European Parliament and of the Council on general product safety.

Certification was carried out by Notified Body No. 2834 (CCQS Certification Services Limited, Block 1 Blanchardstown Corporate Park, Ballycoolin Road, Blanchardstown, Dublin 15, D15 AKK1, Ireland), **certificate No. CE-PC-230925-253-02-9A**, dated 03/05/2024.

NUMBER OF PIECES IN CARTON	120 pc
CARTON WEIGHT	7 kg
CARTON SIZE	0,05 m ³
UNIT PACKAGING	1 pc

The product must be stored in its packaging in a dry, clean place, away from direct sunlight, at temperatures between +5°C and +55°C, with relative humidity up to 90%, and away from sources of gasoline or solvent vapors. Cleaning is recommended after each use. Clean at room temperature using a soft cloth lightly moistened with a diluted solution of water and mild detergent. Do not use hot water, gasoline, degreasers, organic solvents, or abrasive cleaning agents.