



ARDON®
WORKWEAR
& OUTDOOR

ARDON® AKEAN S7S ESD

SAFETY SHOES



REFLECTIVE



WATER
REPELLENT



DEFUSE
CONTROL



NONMETALLIC



ESD

TECHNICAL SHEET



ARDON®
WORKWEAR
& OUTDOOR

ARDON® AKEAN S7S ESD

SAFETY SHOES

ARTICLE

G3489

MATERIAL

Upper MICROFIBER synthetic fibre/CRAZY HORSE leather/TPU
Lining COMFORT MEMBRANE
Outsole PU/Rubber, dual-density injection
Toe cap Fiberglass
Plate Kevlar
Insole PU/MESH textile

SIZE

36-48

UNIT

pair

PACKAGE

Units in a carton 10 pairs
Units in a box 1 pair

DIMENSIONS

	36-42	43-48
Carton H x W x D (cm)	34 x 53,5 x 62	37,5 x 57,5 x 64
Carton (cbm)	0,1128	0,1380

Size EUR	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51
Insole length mm	240	247	253	260	267	273	280	287	293	300	307	313	320	-	-	-
Foot length cm	23,0	23,7	24,3	25,0	25,7	26,3	27,0	27,7	28,3	29,0	29,7	30,3	31,0	-	-	-

DESCRIPTION

Safety footwear with a full-grain Crazy Horse leather upper combined with microfiber and TPU. The waterproof COMFORT MEMBRANE ensures protection against moisture and provides an optimal internal climate. Outsole made of dual-density injected PU/rubber with high slip resistance. Toe protection is provided by a fiberglass toe cap, while a non-metallic Kevlar midsole protects against punctures. Anatomical PU/Mesh insole with a shock-absorbing construction.

TECHNICAL SHEET

NORMS

(EU) 2016/425

EN ISO 20345:2022+A1:2024

EN IEC 61340-4-3:2018

Personal protective equipment - Safety footwear
Electrostatics: Standard test methods for specific
application – Footwear

Category:

S7S LG CI SC FO SR ESD

Categories

EN ISO 20345

E - energy absorption in the heel area

✓



FO - resistance to oils and fuels

✓



A - antistatic footwear

✓



SR - resistance to slipping on ceramic floor tiles with SLS
and on steel floors with glycerin

✓



WPA - Water penetration and absorption

✓



Safety toe cap for toe protection

✓



P - resistance to punctures (protective insole)

✓



The shoes do not contain metal parts

✓



HRO - resistance to contact heatup to 300 °C



insulation of the bottom of the shoe against heat



insulation of the bottom of the shoe against the cold

✓



Splatters of molten metal



ESD – shoe protects against electrostatic discharge and can
be used on EPA premises

✓



LG – Ladder Grip

✓



-

-

-



ARDON®
WORKWEAR
& **OUTDOOR**

CODE	EAN	CARTON WEIGHT (KG)	UNIT WEIGHT (KG)
G3489/36	8592390376640	15,25	1,525
G3489/37	8592390376657	15,6	1,56
G3489/38	8592390376664	15,92	1,592
G3489/39	8592390376671	16,27	1,627
G3489/40	8592390376688	16,61	1,661
G3489/41	8592390376695	17,07	1,707
G3489/42	8592390376701	17,35	1,735
G3489/43	8592390376763	17,71	1,771
G3489/44	8592390376770	18	1,8
G3489/45	8592390376787	18,5	1,85
G3489/46	8592390376794	18,75	1,875
G3489/47	8592390376800	18,97	1,897
G3489/48	8592390376817	19,2	1,92



ARDON®
WORKWEAR
& OUTDOOR





ARDON®

**SHOEWEAR
OUTDOOR**



TECHNICAL SHEET

© ARDON s.r.o. / ALL RIGHTS RESERVED

ARDON s.r.o. tř. Kosmonautů 1221/2a, Olomouc www.ardon.cz