



ARDON®
WORKWEAR
& OUTDOOR

ARDON® AKEAN LOW S7S ESD

SAFETY SHOES



REFLECTIVE



WATER
REPELLENT



DEFUSE
CONTROL



NONMETALLIC



ESD

TECHNICAL SHEET



ARDON®
WORKWEAR
& OUTDOOR

ARDON® AKEAN LOW S7S ESD

SAFETY SHOES

ARTICLE

G3490

MATERIAL

Upper MICROFIBER synthetic fibre/CRAZY HORSE leather/TPU
Lining COMFORT MEMBRANE
Outsole PU/Rubber, dual-density injection
Toe cap Fiberglass
Plate Kevlar
Insole PU/MESH textile

SIZE

36-48

UNIT

pair

PACKAGE

Units in a carton 10 pairs
Units in a box 1 pair

DIMENSIONS

	36-42	43-48
Carton H x W x D (cm)	34 x 45,5 x 62	37,5 x 47,5 x 64,5
Carton (cbm)	0,0959	0,1149

Size EUR	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51
Insole length mm	240	247	253	260	267	273	280	287	293	300	307	313	320	-	-	-
Foot length cm	23,5	24,2	24,8	25,5	26,2	26,8	27,5	28,2	28,8	29,5	30,2	30,8	31,5	-	-	-

DESCRIPTION

Safety footwear with a full-grain Crazy Horse leather upper combined with microfiber and TPU. The waterproof COMFORT MEMBRANE ensures protection against moisture and provides an optimal internal climate. Outsole made of dual-density injected PU/rubber with high slip resistance. Toe protection is provided by a fiberglass toe cap, while a non-metallic Kevlar midsole protects against punctures. Anatomical PU/Mesh insole with a shock-absorbing construction.

TECHNICAL SHEET

NORMS

(EU) 2016/425

EN ISO 20345:2022+A1:2024

EN IEC 61340-4-3:2018

Personal protective equipment - Safety footwear
Electrostatics: Standard test methods for specific
application – Footwear

Category:

S7S LG CI SC FO SR ESD

Categories

EN ISO 20345

E - energy absorption in the heel area

✓



FO - resistance to oils and fuels

✓



A - antistatic footwear

✓



SR - resistance to slipping on ceramic floor tiles with SLS
and on steel floors with glycerin

✓



WPA - Water penetration and absorption

✓



Safety toe cap for toe protection

✓



P - resistance to punctures (protective insole)

✓



The shoes do not contain metal parts

✓



HRO - resistance to contact heatup to 300 °C



insulation of the bottom of the shoe against heat



insulation of the bottom of the shoe against the cold

✓



Splatters of molten metal



ESD – shoe protects against electrostatic discharge and can
be used on EPA premises

✓



LG – Ladder Grip

✓



-

-

-



ARDON®
WORKWEAR
& **OUTDOOR**

CODE	EAN	CARTON WEIGHT (KG)	UNIT WEIGHT (KG)
G3490/36	8592390376978	14,37	1,437
G3490/37	8592390376992	14,69	1,469
G3490/38	8592390377005	15,07	1,507
G3490/39	8592390377012	15,32	1,532
G3490/40	8592390377029	15,7	1,57
G3490/41	8592390377036	16,15	1,615
G3490/42	8592390377043	16,47	1,647
G3490/43	8592390377050	16,8	1,68
G3490/44	8592390377067	17,11	1,711
G3490/45	8592390377074	17,55	1,755
G3490/46	8592390377128	17,78	1,778
G3490/47	8592390377135	18,07	1,807
G3490/48	8592390377142	18,3	1,83



ARDON®
WORKWEAR
& OUTDOOR





ARDON®
WORKWEAR
& OUTDOOR



TECHNICAL SHEET