ARDON®
WORKWEAR
& OUTDOOR

ARDON® APGRADE OB

WORKING SHOES



TECHNICAL SHEET



WASH-FRIENDLY



DRY AIR



DEFUSE CONTROL



NONMETALLIC

© ARDON s.r.o. / ALL RIGHTS RESERVED
ARDON s.r.o. tř. Kosmonautů 1221/2a, Olomouc www.ardon.cz

ARDON® APGRADE OB

WORKING SHOES



ARTICLE	**G3494**
Color	blue
MATERIAL	
Upper	Two-layer knitted textile type 3D KNIT
Lining	Laminated breathable MESH textile
SOLE	Expanded Rubber, single-density injection
Toe cap	x
Plate	x
Insole	Anatomically shaped insole, PU FOAM
SIZE	36-48
UNIT	pair
PACKAGE	
Units in a carton	10 pairs
Units in a box	1 pair

DIMENSIONS	36-41	42-48
Carton H x W x D (cm)	59x48,5x32	64x50x36,5
Carton (cbm)	0,092	0,117

Size EUR	**36**	**37**	**38**	**39**	**40**	**41**	**42**	**43**	**44**	**45**	**46**	**47**	**48**
Insole length mm	24,0	24,7	25,4	26,0	26,7	27,4	28,1	28,7	29,4	30,1	30,7	31,4	32,1
Foot length cm	23,5	24,2	24,9	25,5	26,2	26,9	27,6	28,2	28,9	29,6	30,2	30,9	31,6

DESCRIPTION

Sporty design work shoe featuring a 3D knit textile upper, laminated breathable MESH lining, lightweight expanded rubber outsole, and an automatically shaped footbed made of PU foam.

TECHNICAL SHEET

© ARDON s.r.o. / ALL RIGHTS RESERVED
ARDON s.r.o. tř. Kosmonautů 1221/2a, Olomouc www.ardon.cz

NORMS

(EU) 2016/425
EN ISO 20347:2022+A1:2024 Personal protective equipment – Occupational footwear
Category: OB E SR



Categories	EN ISO 20347	
E - energy absorption in the heel area	✓	
FO - resistance to oils and fuels		
A - antistatic footwear		
SR - resistance to slipping on ceramic floor tiles with SLS and on steel floors with glycerin	✓	SR
The shoes do not contain metal parts	✓	0% METAL
Safety toe cap for toe protection		
P - resistance to punctures (protective insole)		
WPA - Water penetration and absorption		WPA
HRO - resistance to contact heatup to 300 °C		300 °C
HI-insulation of the bottom of the shoe against heat		HI
CI-insulation of the bottom of the shoe against the cold		CI
Splatters of molten metal		WG
ESD – shoe protects against electrostatic discharge and can be used on EPA premises		
-		
-		
-		

TECHNICAL SHEET

© ARDON s.r.o. / ALL RIGHTS RESERVED
ARDON s.r.o. tř. Kosmonautů 1221/2a, Olomouc www.ardon.cz

CODE	EAN	CARTON WEIGHT (KG)	UNIT WEIGHT (KG)
G3494/36	8592390403636	9,5	0,95
G3494/37	8592390403643	9,7	0,97
G3494/38	8592390403650	9,9	0,99
G3494/39	8592390403667	10,1	1,01
G3494/40	8592390403674	10,3	1,03
G3494/41	8592390403681	10,6	1,06
G3494/42	8592390403698	10,9	1,09
G3494/43	8592390403704	12	1,20
G3494/44	8592390403711	12,2	1,22
G3494/45	8592390403728	12,4	1,24
G3494/46	8592390403735	12,6	1,26
G3494/47	8592390403742	12,8	1,28
G3494/48	8592390403759	13,0	1,30



© ARDON s.r.o. / ALL RIGHTS RESERVED

ARDON®
WORKWEAR
& OUTDOOR



© ARDON s.r.o. / ALL RIGHTS RESERVED
ARDON s.r.o. tř. Kosmonautů 1221/2a, Olomouc www.ardon.cz

ARDON®
WORKWEAR
& OUTDOOR







© ARDON s.r.o. / ALL RIGHTS RESERVED
ARDON s.r.o. tř. Kosmonautů 1221/2a, Olomouc www.ardon.cz