



ARDON®
WORKWEAR
& OUTDOOR

ARDON® ULTRITE® S3S WINTER

SAFETY SHOES



**WATER
REPELLENT**



WINTER

TECHNICAL SHEET



ARDON®
WORKWEAR
& OUTDOOR

ARDON® ULTRITE® S3S WINTER

SAFETY SHOES

ARTICLE

G3528

MATERIAL

Upper

Split Nubuck/TPU

Lining

3M Thinsulate insulation

Sole

Rubber

Toe cap

Fibreglass

Plate

Kevlar

Insole

K208 mesh + high density PU

SIZE

35-50

UNIT

pair

PACKAGE

Units in a carton

10 pairs

Units in a box

1 pair

DIMENSIONS

35-43

44-50

Carton H x W x D (cm)

33,5 x 51,5 x 61,5

38,5 x 53,5 x 66,5

Carton (cbm)

0,106

0,137

Size EUR	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50
Insole length mm	230	237	244	250	257	264	270	277	284	290	297	304	310	317	324	329
Foot length cm	22,5	23,2	23,9	24,5	25,2	25,9	26,5	27,2	27,9	28,5	29,2	29,9	30,5	31,2	31,9	32,4

DESCRIPTION

High-performance insulated winter ankle safety footwear featuring a premium black upper with an SC (scuff cap) protective element for enhanced durability. Warm lining provides excellent thermal comfort in cold environments. Injected outsole ensures superior shock absorption, flexibility, slip resistance (SR) and resistance to contact heat up to 300 °C (HRO). Equipped with thermal insulation against cold (CI) and heat (HI), ladder grip (LG) support, fiberglass toe cap and non-metallic anti-perforation textile midsole (S3S). Designed for demanding winter and outdoor applications requiring reliable protection, stability and comfort.

NORMS

(EU) 2016/425

EN ISO 20345:2022+A1:2024

Personal protective equipment –Safety footwear

Category

S3S SR FO HRO SC CI HI LG

Categories

EN ISO 20345

E - energy absorption in the heel area

✓



FO - resistance to oils and fuels

✓



A - antistatic footwear

✓



SR - resistance to slipping on ceramic floor tiles with SLS
and on steel floors with glycerin

✓



WPA - water penetration and absorption

✓



Safety toe cap for toe protection

✓



P - resistance to punctures (protective insole)

✓



The shoes do not contain metal parts



HRO - resistance to contact heatup to 300 °C

✓



HI-insulation of the bottom of the shoe against heat

✓



CI-insulation of the bottom of the shoe against the cold

✓



Splatters of molten metal



ESD – shoe protects against electrostatic discharge and can
be used on EPA premises



-

-

-



ARDON®
WORKWEAR
& **OUTDOOR**

CODE	EAN	CARTON WEIGHT (KG)	UNIT WEIGHT (KG)
G3528/35	8592390417428	13,05	1,305
G3528/36	8592390417435	13,5	1,35
G3528/37	8592390417442	13,98	1,398
G3528/38	8592390417459	14,88	1,488
G3528/39	8592390417466	15,16	1,516
G3528/40	8592390417473	15,48	1,548
G3528/41	8592390417480	16,64	1,664
G3528/42	8592390417497	16,9	1,69
G3528/43	8592390417503	17,66	1,766
G3528/44	8592390417510	18,42	1,842
G3528/45	8592390417527	18,86	1,886
G3528/46	8592390417534	19,36	1,936
G3528/47	8592390417541	20,06	2,006
G3528/48	8592390417558	20,46	2,046
G3528/49	8592390417565	21,06	2,106
G3528/50	8592390417572	21,66	2,166



ARDON®
WORKWEAR
& OUTDOOR





ARDON®
WORKWEAR
& OUTDOOR

