ARDON®
WORKWEAR
& OUTDOOR

ARDON®ULTRITE®O2

WORKING SHOES



TECHNICAL SHEET

DEFUSE CONTROL

WATER REPELLENT

© ARDON s.r.o. / ALL RIGHTS RESERVED
ARDON s.r.o. tř. Kosmonautů 1221/2a, Olomouc www.ardon.cz

ARDON®ULTRITE®O2

WORKING SHOES



ARTICLE	**G3529**
MATERIAL	
Upper	ACTION NUBUK – cowhide leather/PU/textile
Lining	Laminated breathable MESH textile
Sole	PU/RUBBER, dual-density injection
Insole	Anatomical foam
SIZE	38-48
UNIT	pair
PACKAGE	
Units in a carton	10 pairs
Units in a box	1 pair

DIMENSIONS	38-43	44-48
Carton H x W x D (cm)	33.5 x 51.5 x 61.5	38.5 x 53.5 x 66.5
Carton (cbm)	0,106	0,137

Size EUR	**38**	**39**	**40**	**41**	**42**	**43**	**44**	**45**	**46**	**47**	**48**
Insole length mm	250	257	264	270	277	284	290	297	304	310	317
Foot length cm	24,0	24,7	25,4	26,0	26,7	27,4	28,0	28,7	29,4	30,0	30,7

TECHNICAL SHEET

DESCRIPTION

Occupational ankle footwear with an upper made of ACTION NUBUK – cowhide leather/PU/textile. The injected sole has SR slip-resistant properties and is resistant to contact heat up to 300°C (HRO). The anatomical foam insole ensures increased footwear comfort. The footwear features cold insulation (CI) and heat insulation (HI).

© ARDON s.r.o. / ALL RIGHTS RESERVED
ARDON s.r.o. tř. Kosmonautů 1221/2a, Olomouc www.ardon.cz

NORMS

(EU) 2016/425
EN ISO 20347:2022+A1:2024 Personal protective equipment – Occupational footwear

Category O2 SR FO HRO SC CI HI LG

Categories	**EN ISO 20347**	
E - energy absorption in the heel area	✓	
FO - resistance to oils and fuels	✓	
A - antistatic footwear	✓	
SR - resistance to slipping on ceramic floor tiles with SLS and on steel floors with glycerin	✓	SR
WPA – water penetration and absorption	✓	WPA
Safety toe cap for toe protection		
P - resistance to punctures (protective insole)		
HRO - resistance to contact heatup to 300 °C	✓	300 °C
HI-insulation of the bottom of the shoe against heat	✓	HI
CI-insulation of the bottom of the shoe against the cold	✓	CI
Splatters of molten metal		WG
ESD – shoe protects against electrostatic discharge and can be used on EPA premises		ESD
The shoes do not contain metal parts		0% METAL
-		
-		
-		

TECHNICAL SHEET

© ARDON s.r.o. / ALL RIGHTS RESERVED
ARDON s.r.o. tř. Kosmonautů 1221/2a, Olomouc www.ardon.cz

CODE	EAN	CARTON WEIGHT (KG)	UNIT WEIGHT (KG)
G3529/38	8592390417749	12,26	1,226
G3529/39	8592390417763	12,46	1,246
G3529/40	8592390417787	12,68	1,268
G3529/41	8592390417800	13,26	1,326
G3529/42	8592390417824	14,06	1,406
G3529/43	8592390417848	14,16	1,416
G3529/44	8592390417862	15,12	1,512
G3529/45	8592390417886	15,5	1,55
G3529/46	8592390417909	15,9	1,59
G3529/47	8592390417923	16,44	1,644
G3529/48	8592390417947	17,2	1,72



© ARDON s.r.o. / ALL RIGHTS RESERVED
ARDON s.r.o. tř. Kosmonautů 1221/2a, Olomouc www.ardon.cz

ARDON®
WORKWEAR
& OUTDOOR



© ARDON s.r.o. / ALL RIGHTS RESERVED
ARDON s.r.o. tř. Kosmonautů 1221/2a, Olomouc www.ardon.cz

ARDON®
WORKWEAR
& OUTDOOR







© ARDON s.r.o. / ALL RIGHTS RESERVED