ARDON®
WORKWEAR
& OUTDOOR

ARDON®ULTRITE®O2 LOW

WORKING SHOES



TECHNICAL SHEET

DEFUSE CONTROL

WATER REPELLENT

© ARDON s.r.o. / ALL RIGHTS RESERVED
ARDON s.r.o. tř. Kosmonautů 1221/2a, Olomouc www.ardon.cz

ARDON®ULTRITE®O2 LOW

WORKING SHOES



ARTICLE	**G3530**
Color	Brown
MATERIAL	
Upper	ACTION NUBUK – cowhide leather/PU/textile
Lining	Laminated breathable MESH textile
SOLE	PU/RUBBER, dual-density injection
Toe cap	x
Plate	x
Insole	Anatomical foam
SIZE	38-48
UNIT	pair
PACKAGE	
Units in a carton	10 pairs
Units in a box	1 pair

DIMENSIONS	38-43	44-48
Carton H x W x D (cm)	61,5x43,5x33,5	66,5x45,5x38,5
Carton (cbm)	0,0896	0,1165

Size EUR	**38**	**39**	**40**	**41**	**42**	**43**	**44**	**45**	**46**	**47**	**48**
Insole length mm	250	257	264	270	277	284	290	297	304	310	317
Foot length cm	24,5	25,2	25,9	26,5	27,2	27,9	28,5	29,2	29,9	30,5	31,2

DESCRIPTION

Durable low-cut O2 occupational shoe featuring a premium brown upper made of action nubuck, cowhide leather, PU, and textile. The injected PU/RUBBER outsole provides effective shock absorption, flexibility, reliable slip resistance (SR), and contact heat resistance up to 300 °C (HRO). It includes advanced thermal insulation against cold (CI) and heat (HI), alongside a specialized ladder grip (LG) for safe climbing. Designed to provide high comfort, agility, terrain stability, and advanced weather/surface protection in demanding environments such as logistics, outdoor maintenance, warehousing, service operations, or light manufacturing.

TECHNICAL SHEET

© ARDON s.r.o. / ALL RIGHTS RESERVED
ARDON s.r.o. tř. Kosmonautů 1221/2a, Olomouc www.ardon.cz

NORMS

(EU) 2016/425
EN ISO 20347:2022+A1:2024 Personal protective equipment – Occupational footwear



Category: O2 SR FO HRO CI HI LG

Categories	**EN ISO 20347**	
E - energy absorption in the heel area	✓	
FO - resistance to oils and fuels	✓	
A - antistatic footwear	✓	
SR - resistance to slipping on ceramic floor tiles with SLS and on steel floors with glycerin	✓	SR
The shoes do not contain metal parts		0% METAL
Safety toe cap for toe protection		
P - resistance to punctures (protective insole)		
WPA - Water penetration and absorption	✓	WPA
HRO - resistance to contact heatup to 300 °C	✓	300 °C
HI-insulation of the bottom of the shoe against heat	✓	HI
CI-insulation of the bottom of the shoe against the cold	✓	CI
Splatters of molten metal		WG
ESD – shoe protects against electrostatic discharge and can be used on EPA premises		
-		
-		
-		

TECHNICAL SHEET

© ARDON s.r.o. / ALL RIGHTS RESERVED
ARDON s.r.o. tř. Kosmonautů 1221/2a, Olomouc www.ardon.cz

CODE	EAN	CARTON WEIGHT (KG)	UNIT WEIGHT (KG)
G3530/38	8592390417961	11,4	1,14
G3530/39	8592390417978	11,58	1,158
G3530/40	8592390417985	11,86	1,186
G3530/41	8592390417992	12,38	1,238
G3530/42	8592390418005	13,04	1,304
G3530/43	8592390418012	13,18	1,318
G3530/44	8592390418029	14,22	1,422
G3530/45	8592390418036	14,75	1,475
G3530/46	8592390418043	15,02	1,502
G3530/47	8592390418050	15,54	1,554
G3530/48	8592390418067	16,01	1,601



© ARDON s.r.o. / ALL RIGHTS RESERVED
ARDON s.r.o. tř. Kosmonautů 1221/2a, Olomouc www.ardon.cz

ARDON®
WORKWEAR
& OUTDOOR



© ARDON s.r.o. / ALL RIGHTS RESERVED
ARDON s.r.o. tř. Kosmonautů 1221/2a, Olomouc www.ardon.cz

ARDON®
WORKWEAR
& OUTDOOR







© ARDON s.r.o. / ALL RIGHTS RESERVED