ARDON®
WORKWEAR
& OUTDOOR

ARDON®ASONEX AIR O1 ESD

WORKING SHOES

TECHNICAL SHEET





DEFUSE CONTROL | DRY AIR | NONMETALLIC | REFLECTIVE

© ARDON.s.r.o. / ALL RIGHTS RESERVED

ARDON® ASONEX AIR O1 ESD

WORKING SHOES



ARTICLE	**G3500**
MATERIAL	
Upper	Nylon Mesh Coating TPU
Lining	K208 Mesh
Outsole	Rubber, cemented technology
Toe cap	
Plate	
Insole	Mesh + HI-Poly
SIZE	36-48
UNIT	pair
PACKAGE	
Units in a carton	10 pairs
Units in a box	1 pairs

DIMENSIONS	36-43	41-44
Carton H x W x D (cm)	43,5 x 61,5 x 33,5	45,5 x 66,5 x 38,5
Carton (cbm)	0,090	0,116

Size EUR	**35**	**36**	**37**	**38**	**39**	**40**	**41**	**42**	**43**	**44**	**45**	**46**	**47**	**48**	**49**	**50**	**51**
Insole length mm	-	232	239	245	252	259	265	272	279	285	292	299	305	312	-	-	-
Foot length cm	-	22,7	23,4	24,5	24,7	25,4	26	26,7	27,4	28	28,7	29,4	30	30,7	-	-	-

DESCRIPTION

Ultra-lightweight sports-style work shoes featuring a nylon MESH upper with a TPU coating and a cemented rubber outsole. The footwear is equipped with a comfortable Hi-Poly insole.

TECHNICAL SHEET

© ARDON s.r.o. / ALL RIGHTS RESERVED
ARDON s.r.o. tř. Kosmonautů 1221/2a, Olomouc www.ardon.cz

NORMS

(EU) 2016/425

EN ISO 20347:2022+A1:2024	Personal protective equipment – occupational footwear
EN61340-5-1:2024	Electrostatics: Standard test methods for specific application - Footwear

Category: O1 SR ESD

Categories	**EN ISO 20347**	
E – energy absorption in the heel area	✓	
FO – resistence to oils and fuels		
A – antistatic footwear	✓	
SR – resistence to slipping on ceramic floor tiles with SLS and on steel floors with glycerin	✓	SR
WR – upper resistant to water		H_2O
Safety toe cap for toe protection		
P – resistence to punctures (protective insoles)		
HRO – resistence to contact heatup to 300 °C		300 °C
HI – insulation of the bottom of the shoe against heat		HI
CI – insulation of the bottom of the shoe against the cold		CI
Splatters of molten metal		WG
ESD – shoe protects against electrostatic discharge and can be used on EPA premises	✓	ESD
The shoe do not contain metal parts	✓	0% METAL
-		
-		
-		
-		

TECHNICAL SHEET

© ARDON s.r.o. / ALL RIGHTS RESERVED
ARDON s.r.o. tř. Kosmonautů 1221/2a, Olomouc www.ardon.cz

Code	EAN	Carton – weight (KG)	Unit weight (KG)
G3500/36	8592390406637	8,7	0,87
G3500/37	8592390406644	8,95	0,895
G3500/38	8592390406651	9,1	0,91
G3500/39	8592390406668	9,45	0,945
G3500/40	8592390406675	9,65	0,965
G3500/41	8592390406682	9,95	0,995
G3500/42	8592390406699	10,2	1,02
G3500/43	8592390406705	10,9	1,09
G3500/44	8592390406712	11,15	1,115
G3500/45	8592390406729	11,6	1,16
G3500/46	8592390406736	11,95	1,195
G3500/47	8592390406743	12	1,2
G3500/48	8592390406750	12,1	1,21



© ARDON s.r.o. / ALL RIGHTS RESERVED
ARDON s.r.o. tř. Kosmonautů 1221/2a, Olomouc www.ardon.cz

ARDON®
WORKWEAR
& OUTDOOR



© ARDON s.r.o. / ALL RIGHTS RESERVED
ARDON s.r.o. tř. Kosmonautů 1221/2a, Olomouc www.ardon.cz

ARDON®
WORKWEAR
& OUTDOOR

TECHNICAL SHEET







© ARDON s.r.o. / ALL RIGHTS RESERVED
ARDON s.r.o. tř. Kosmonautů 1221/2a, Olomouc www.ardon.cz