ARDON®
WORKWEAR
& OUTDOOR

ARDON®ROVERWIN S3

SAFETY SHOES



WINTER

FOOT COMFORT

WATER REPELLENT

TECHNICAL SHEET

© ARDON s.r.o. / ALL RIGHTS RESERVED
ARDON s.r.o. tř. Kosmonautů 1221/2a, Olomouc www.ardon.cz

ARDON®ROVERWIN S3

SAFETY SHOES

ARTICLE	**G3390**
MATERIAL	
Upper	ACTION NUBUK- cowhide leather with polyurethane coating, hydrophobic
Lining	synthetic fur
Sole	PU/rubber, two-component spray coating, oil resistant, anti-static, antislip, resistant up to 300 ° C
Toe cap	composite 431
Plate	kevlar
Insole	ANATOMIC FOAM – anatomically shaped EVA foam, supports longitudinal and transverse arches, absorbs shocks in the heel area
SIZE	35-50
UNIT	pair
PACKAGE	10 pairs
Units in a carton	1 pair
Units in a box	

DIMENSIONS	35-38	39-43	44-48	49-50
Carton H x W x D (cm)	64,5x 34 x 43,5	64,5x 34 x 51,5	67x38x55,5	69,5x41x57,5
Carton (cbm)	0,0954	0,1129	0,1413	0,1638

Size EUR	**35**	**36**	**37**	**38**	**39**	**40**	**41**	**42**	**43**	**44**	**45**	**46**	**47**	**48**	**49**	**50**	**51**
Insole length mm	232	239	246	253	259	266	273	280	287	293	300	306	313	319	325	332	-
Foot length cm	22,2	22,9	23,6	24,3	24,9	25,6	26,3	27	27,7	28,3	29	29,6	30,3	30,9	31,5	32,2	-

DESCRIPTION

Safety shoes with an extra wide sole, resistant to contact heat up to 300 ° C and with an upper made of leather with a PU coating. The ANATOMIC FOAM insole ensures increased comfort of the shoes. The shoes are equipped with a composite toe cap and a kevlar insole against punctures.

TECHNICAL SHEET

© ARDON s.r.o. / ALL RIGHTS RESERVED

NORMS

(EU) 2016/425
EN ISO 20345:2022+A1:2024 Personal protective equipment - Safety footwear

Category S3L HI CI SR HRO FO



Categories	**EN ISO 20345**	
E - energy absorption in the heel area	✓	
FO - resistance to oils and fuels	✓	
A - antistatic footwear	✓	
SR - resistance to slipping on ceramic floor tiles with SLS and on steel floors with glycerin	✓	SR
WPA - upper resistant to water	✓	WPA
Safety toe cap for toe protection	✓	
P - resistance to punctures (protective insole)	✓	
The shoes do not contain metal parts		0% METAL
HRO - resistance to contact heatup to 300 °C	✓	300 °C
HI-insulation of the bottom of the shoe against heat	✓	HI
CI-insulation of the bottom of the shoe against the cold	✓	CI
Splatters of molten metal		WG
ESD – shoe protects against electrostatic discharge and can be used on EPA premises		ESD
-		
-		
-		

TECHNICAL SHEET

© ARDON s.r.o. / ALL RIGHTS RESERVED
ARDON s.r.o. tř. Kosmonautů 1221/2a, Olomouc www.ardon.cz

CODE	EAN	CARTON WEIGHT (KG)	UNIT WEIGHT (KG)
G3390/35	8592390154293	19.2	1.920
G3390/36	8592390154309	19.3	1.925
G3390/37	8592390154316	19.3	1.930
G3390/38	8592390154323	19.4	1.935
G3390/39	8592390154330	19.4	1.940
G3390/40	8592390154347	19.5	1.945
G3390/41	8592390154354	19.6	1.959
G3390/42	8592390154361	19.8	1.975
G3390/43	8592390154378	19.8	1.981
G3390/44	8592390154385	19.8	1.983
G3390/45	8592390154392	19.9	1.988
G3390/46	8592390154408	19.9	1.989
G3390/47	8592390154415	19.9	1.990
G3390/48	8592390154422	20.0	2.000
G3390/49	8592390154439	20.5	2.050
G3390/50	8592390154446	20.9	2.090



© ARDON s.r.o. / ALL RIGHTS RESERVED

ARDON®
WORKWEAR
& OUTDOOR



© ARDON s.r.o. / ALL RIGHTS RESERVED

ARDON®
WORKWEAR
& OUTDOOR







© ARDON s.r.o. / ALL RIGHTS RESERVED